



Bridge clamp for attaching externally corrugated spiral hoses

Properties

- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted
- re-usable
- conforms to RoHS guideline

Design, material

Quality: W2; clamp strip: stainless steel 1.4301 = AISI 304; screw: galvanised steel; Body: stainless steel 1.4016 = AISI 430; bridge: stainless steel 1.4301 = AISI 304 (INOX)

Delivery variants

- further diameters available on request

Suitable for hose

AIRDUC®: 341 + 345 + 363; 350 (AS/ FOOD-AS / AS BLACK); 351 + 355 (FOOD / INOX FOOD-AS / HT-PUR); 351 + 355 EC; 352 (SE RAILWAY / SE RAILWAY PLUS); 355 AS; 362 (FOOD / EC); PROTAPÉ®: 330 (FOOD / BLACK / INOX FOOD - AS); 301 AS; 310 + 320 + 321 + 326 + 327 + 332;

322 EC;

CP: 450 + 455 + 457 + 460 + 461 + 465 + 466 + 467 + 476 + 480 + 481 + 483 + 485 + 486 + 487; 450 + 461 PROTECT; 457 + 459 + 465 EC; 471 + 472 + 475 (INOX / INOX EC); TIMBERDUC®: 531 - 533 AS

Suitable for hose I.D. Inch	Clamping range Inch	Band width Inch	Order No.
AIRDUC® & PROTAPÉ® ≤ 1.75 in			
0.50 - 0.63	0.35 - 0.75	0.20	212-0009-0000
0.59 - 0.71	0.50 - 0.79	0.20	212-0013-0000
0.71 - 1.02	0.67 - 1.14	0.20	212-0017-0000
7/8 - 1.10	0.79 - 1.10	0.20	212-0020-0000
1.00 - 1.14	7/8 - 1.46	0.35	212-0022-0000
1 1/8 - 1.36	1.06 - 1.85	0.35	212-0027-0000
1.25 - 1.46	1.14 - 1.85	0.35	212-0029-0000
1.50 - 1.73	1.36 - 2.17	0.35	212-0035-0000
CP Ø 1.5 in - 2.55 in, PROTAPÉ® TPE 326 MEMORY Ø 2.0-2.55 in			
1.50 - 1.75	1.36 - 2.17	0.35	212-0035-2002
1.77-1.97	1.57-2.36	0.35	212-0040-2002
1.97-2.16	1.77-2.56	0.35	212-0045-2002
2.36-2.56	2.16-2.95	0.35	212-0055-2002
AIRDUC® & PROTAPÉ® ≥ 1.75 in, CP & PROTAPÉ® TPE 326 MEMORY ≥ 2.75 in			
1.75 - 2.00	1.57 - 2.36	0.35	212-0040-0000
2.00 - 2.17	1.75 - 2.50	0.35	212-0045-0000
2.36 - 2.50	2.17 - 3.00	0.35	212-0055-0000
2.76 - 3.00	2.50 - 3.35	0.35	212-0065-0000
3.15 - 3.35	3.00 - 3.74	0.35	212-0075-0000
3.50 - 3.74	3.35 - 4.13	0.35	212-0085-0000
4.00 - 4.13	3.74 - 4.50	0.35	212-0095-0000
4.33 - 4.50	4.13 - 5.00	0.35	212-0105-0000
4.72 - 5.00	4.50 - 5.31	0.35	212-0115-0000
5.12 - 5.31	5.00 - 5.71	0.35	212-0125-0000
5.50 - 5.71	5.31 - 6.10	0.35	212-0135-0000
6.00 - 6.10	5.71 - 6.50	0.35	212-0145-0000

We reserve the right to make technical changes. All values have been determined at 68°F and are approx. values.

CLAMP 212

Suitable for hose I.D. Inch	Clamping range Inch	Band width Inch	Order No.
6.30 - 6.50	6.10 - 6.89	0.35	212-0155-0000
6.69 - 6.89	6.50 - 7.28	0.35	212-0165-0000
7.00 - 7.28	6.89 - 7.68	0.35	212-0175-0000
7.48 - 7.68	7.28 - 8.07	0.35	212-0185-0000
8.00 - 8.07	7.68 - 8.46	0.35	212-0195-0000
8.27 - 8.46	8.07 - 8.86	0.47	212-0205-0000
8.66 - 8.86	8.46 - 9.25	0.47	212-0215-0000
9.06 - 9.25	8.86 - 9.65	0.47	212-0225-0000
9.45 - 9.65	9.25 - 10.04	0.47	212-0235-0000
9.84 - 10.04	9.65 - 10.43	0.47	212-0245-0000
10.24 - 10.43	10.04 - 10.83	0.47	212-0255-0000
10.63 - 10.83	10.43 - 11.22	0.47	212-0265-0000
11.00 - 11.22	10.83 - 11.61	0.47	212-0275-0000
11.22 - 11.42	11.00 - 11.81	0.47	212-0280-0000
11.42 - 11.61	11.22 - 12.00	0.47	212-0285-0000
11.81 - 12.00	11.61 - 12.40	0.47	212-0295-0000
12.20 - 12.40	12.00 - 12.80	0.47	212-0305-0000
12.60 - 12.80	12.40 - 13.19	0.47	212-0315-0000
13.00 - 13.19	12.80 - 13.58	0.47	212-0325-0000
13.39 - 13.58	13.19 - 13.98	0.47	212-0335-0000
13.78 - 13.98	13.58 - 14.37	0.47	212-0345-0000
14.17 - 14.37	13.98 - 14.76	0.47	212-0355-0000
14.57 - 14.76	14.37 - 15.16	0.47	212-0365-0000
14.96 - 15.16	14.76 - 15.55	0.47	212-0375-0000
15.35 - 15.55	15.16 - 15.94	0.47	212-0385-0000
15.75 - 15.94	15.55 - 16.34	0.47	212-0395-0000
16.14 - 16.34	15.94 - 16.73	0.47	212-0405-0000
16.93 - 17.13	16.73 - 17.52	0.47	212-0425-0000
17.72 - 17.91	17.52 - 18.31	0.47	212-0445-0000
18.50 - 18.70	18.31 - 19.09	0.47	212-0465-0000
19.09 - 19.29	18.90 - 19.69	0.47	212-0480-0000
19.69 - 19.88	19.49 - 20.28	0.47	212-0495-0000
20.08 - 21.06	19.88 - 21.46	0.47	212-0505-0000
20.47 - 21.46	20.28 - 21.85	0.47	212-0515-0000
21.65 - 22.64	21.46 - 23.03	0.47	212-0545-0000
22.83 - 23.82	22.64 - 24.21	0.47	212-0575-0000
23.62 - 24.61	23.43 - 25.00	0.47	212-0595-0000
24.80 - 25.79	24.61 - 26.18	0.47	212-0625-0000
25.59 - 26.57	25.39 - 26.97	0.47	212-0645-0000
26.57 - 27.56	26.38 - 27.95	0.47	212-0670-0000
27.56 - 28.54	27.36 - 28.94	0.47	212-0695-0000
28.74 - 29.72	28.54 - 30.12	0.47	212-0725-0000
29.53 - 30.51	29.33 - 30.91	0.47	212-0745-0000
31.50 - 32.48	31.30 - 32.87	0.47	212-0795-0000
32.48 - 33.46	32.28 - 33.86	0.47	212-0820-0000
33.46 - 34.45	33.27 - 34.84	0.47	212-0845-0000
34.65 - 35.63	34.45 - 36.00	0.47	212-0875-0000
35.43 - 36.42	35.24 - 36.81	0.47	212-0895-0000
36.42 - 37.40	36.22 - 37.80	0.47	212-0920-0000
37.40 - 38.39	37.20 - 38.78	0.47	212-0945-0000

Distributed By:

151 Memorial Drive, Unit H
 Shrewsbury, MA 01545
 Tel 888.792.2223
 sales@plastixs.com




CLAMP 212

Suitable for hose I.D. Inch	Clamping range Inch	Band width Inch	Order No.
38.39 - 39.37	38.19 - 39.76	0.47	212-0970-0000
38.98 - 39.96	38.78 - 40.35	0.47	212-0985-0000
41.34 - 42.32	41.14 - 42.72	0.47	212-1045-0000
42.52 - 44.29	42.32 - 44.68	0.47	212-1075-0000

Further diameters available on request. All values indicated here are approximate figures based on a temperature of 68°F. We reserve the right to make technical changes. Please also refer to our Technical Appendix at www.norres.com.

Accessories



CONNECT 228



CONNECT 270-271

Further technical data at www.norres.com. We reserve the right to make technical changes. All values have been determined at 68°F and are approx. values.