

# TECHNICAL DATA SHEET



## Penetrant Plus Aerosol 41812M

### Product Description

Made with non-silicone penetrating oils that are fortified with PTFE additives to increase the lubrication and flow of the product once its applied. It helps free rusted or frozen metal components due to its highly fluid properties that creep into the molecular level of metal. Displaces moisture and leaves behind a protective film to keep parts lubricated and protected from corrosion. Manufactured to be compliant with the strictest California VOC limits.

### Applications

Penetrating Lubricant

### Unit Package Description

16 ounce aerosol

### Generic Description

Penetrating Oil

### Net Weight Fill

12 net ounces

### UPC Code

858799000189

### Appearance

Brown-tint Liquid

### Odor

Petroleum like

### Flash Point F

Not Applicable

### Flash Point C

Not Applicable

### Base Type

Petroleum Oil with PTFE

### Evaporation Rate

Slow

### HMIS Rating

1, 3, 0, B

### DOT Proper Shipping Name

UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

### VOC % (Federal)

21.19

### VOC g/L (Federal)

152.53

### VOC lbs./Gal (Federal)

1.27

### Removal

Remove with organic or hydrocarbon solvents

### Units Per Case

12

### Case Weight (lbs)

13

### Working Temperature F

32 to 338 degrees

### Working Temperature C

0 to 170 degrees

### Propellant

Propane

### NFPA Aerosol Flammability Level

3