


## **TECHNICAL DATA SHEET**





## Pure Eze Mold Release Aerosol 45712N

**Product Description** 

Pure Eze is a white oil-based, food-approved release ideal for medical and food applications. Use Pure Eze with all thermoplastic resins, polyolefins, polycarbonates, rubber and some epoxies. It is colorless, odorless, tasteless and will not change color over time.

| Applications                    | Mold Release  |
|---------------------------------|---|
| Unit Package Description        | 16 ounce aerosol                                    |
| Generic Description             | Paintable Mold Release                              |
| Net Weight Fill                 | 11.5 net ounces                                     |
| UPC Code                        | 858799000578  |
| Appearance                      | Clear Oily Colorless Liquid                         |
| Odor                            | Ether like  |
| Flash Point F                   | Not Applicable                                      |
| Flash Point C                   | Not Applicable                                      |
| Base Type                       | White Oil   |
| Evaporation Rate                | Fast  |
| HMIS Rating                     | 1, 3, 0, B  |
| DOT Proper Shipping Name        | UN 1950, Aerosols, Flammable, 2.1, Limited Quantity |
| VOC % (Federal)                 | 60  |
| VOC g/L (Federal)               | 438.21  |
| VOC lbs./Gal (Federal)          | 3.65  |
| Removal                         | Remove with organic or hydrocarbon solvents         |
| Food Safety Citation (CFR)      | 21CFR 172.878 and 178.3620 (a)                      |
| Units Per Case                  | 12  |
| Case Weight (Ibs)               | 13  |
| Working Temperature F           | 32 to 600 degrees                                   |
| Working Temperature C           | 0 to 315 degrees                                    |
| Propellant                      | DME/152A  |
| NFPA Aerosol Flammability Level | 1   |
| Independent Certifications      | UL recognized                                       |
|                                 |   |