

TECHNICAL DATA SHEET



SLIDE
#400

**PAINTABLE
MOLD
RELEASE**

Safe for use with all plastics
Seguro para ser usado con todos los plásticos

Use where parts must be painted, hot stamped or metalized
Para uso en partes que tienen que pintarse, estamparse al color o metalizarse

Paintable Mold Release Bulk/Liquid 40001PB, 40005PB, 40055PB

Product Description

This paintable mold release is UL recognized and requires no special cleaning. It will not interfere with part bonding, heat sealing, laminating, ultrasonic welding or post-decorating operations. You get perfect finishes every time and more cycles per can over other comparable releases.

Applications

Mold Release

Unit Package Description

1, 5 and 55-gallon containers

Generic Description

Paintable Mold Release

Approx. Net Weight Fill per Gal.

6 pounds

Net Weight Fill

1 - 55 gallons

Appearance

Clear Oily Colorless Liquid

Odor

Mild, Petroleum-like

Flash Point F

25 degrees

Flash Point C

Negative 4 degrees

Base Type

Paintable Silicone Fluid

Evaporation Rate

Fast

HMIS Rating

2, 3, 0, X

DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

VOC % (Federal)

96.67

VOC g/L (Federal)

683.05

VOC lbs./Gal (Federal)

5.7

Removal

Remove with organic or hydrocarbon solvents

Units Per Case

1

Case Weight (lbs)

Various

Working Temperature F

32 to 650 degrees

Working Temperature C

0 to 343 degrees

Specific Gravity

0.698

