

# TECHNICAL DATA SHEET



## Penetrant Plus Bulk/Liquid 41801MB, 41805MB, 41855MB

### Product Description

This mono-molecular penetrating film frees rust-frozen parts. It lifts and replaces moisture with a protective film and lubricates without affecting performance of electrical equipment. Non-conductive because it has high dielectric strength and lubricates delicate electronic equipment.

### Applications

Penetrating Lubricant

### Unit Package Description

1, 5 and 55-gallon containers

### Generic Description

Penetrating Oil

### Approx. Net Weight Fill per Gal.

7 pounds

### Net Weight Fill

1 - 55 gallons

### Appearance

Brownish-Tint Liquid

### Odor

Petroleum like

### Flash Point F

207 degrees

### Flash Point C

97 degrees

### Base Type

Petroleum Oil with PTFE

### Evaporation Rate

Slow

### HMIS Rating

1, 1, 0, Not Determined

### DOT Proper Shipping Name

Not Regulated

### VOC % (Federal)

88

### VOC g/L (Federal)

738.13

### VOC lbs./Gal (Federal)

6.16

### Removal

Remove with organic or hydrocarbon solvents

### Units Per Case

1

### Case Weight (lbs)

Various

### Working Temperature F

32 to 338 degrees

### Working Temperature C

0 to 170 degrees

### Specific Gravity

0.79

